



VENDED STACK DRYER

Huebsch® stack dryer/dryers give your laundry all the benefits of two stand-alone dryers in the space of one machine. The stack utilizes all the same connections as a standard dryers, so there are no special hookups required.

FAST DRYING TIMES

Huebsch dryers offer a 7.0 cu. ft. cylinder with an 18 lb capacity offers ample space for large loads to tumble and produce fast drying times, while lowering utility consumption.

SOLID BASE

Huebsch dryers are built on sturdy steel bases to ensure years of worry-free performance.

SPACE SAVINGS

A stack dryer/dryer gives your vended laundry all the benefits of two stand-alone dryers in the space of one machine. The stack utilizes all the same connections as a standard dryer, so there are no special hookups required.


UNMATCHED DURABILITY

Our vended stack dryer is manufactured at our Ripon, WI headquarters. The entire machine receives Huebsch's standard three-year warranty. In addition, Huebsch has more service representatives in the field than most brands have in their whole organization.

*Parts only, labor not included. See Huebsch Warranty Bond for specifics.



MICRO-DISPLAY CONTROL II



The Micro-Display Control II features a time-remaining countdown, coin countdown and cycle status lights.

VENDED STACK DRYER

Specifications			
Available Controls	MDC II	Coin Slide	
Models	Electric	HSEBCAGW173TW01 HSEBYAGW173TW01 HSEBEAGW293CW01 HSEBDAGW293CW01 HSEBYAGW283CW01 HSEBYAGW293CW01	HSEXAGW173TW01
	Gas	HSGBCAGW113TW01 HSGBYAGW113TW01 HSGBEAGW093CW01 HSGBDAGW093CW01 HSGBXAGW093CW01 HSGBYAGW093CW01	HSGSXAGW113TW01 HSGSXAGW093CW01
Capacity - lb (kg)	18 (8.2)		
Cylinder Volume - cu. Ft. (liters)	7.0 (198)		
Width - in (mm)	26.875 (683)		
Depth - in (mm)	28 (711)		
Height - in (mm)	78.19 (1986)		
Motor Size - HP (kw)	0.33 (0.25)		
Available Heat Sources	Electric or Gas		
Available Heating Element - (Electric W)	4750 @ 208V 5350 @ 240V		
Gas Inlet Connection - in (mm)	3/8 (9.5)		
Gas Consumption - BTU/Hr	25,000		
Exhaust Outlet Diameter - in (mm)	4 (102)		
Exhaust Airflow - cfm (liters/sec)	220 (105)		
Available Cycles*	High, Medium, Low, Delicates		
Cycle Indicator Lights	Yes		
Cylinder Finish	Galvanized		
Available Colors	White		
Door Type (Solid/Window)	Solid or Window		
U.S. Electrical Requirements - (Voltage/Hz/Ph)	Electric: 120/240/60/1 - 30 Amp Electric: 120/208/60/1 - 30 Amp Gas: 120/60/1 - 15 Amp		
Canada Electrical Requirements - Single Supply Cord (Voltage/Hz/Ph)	Electric: 120/240/60/1 - 60 Amp Electric: 120/208/60/1 - 60 Amp Gas: 120/60/1 - 20 Amp		
Net Weight - lb (kg)	Elec/Gas 265/275 (120/125)		
Shipping Weight - lb (kg)	Elec/Gas 280/290 (127/132)		
Shipping Width - in (mm)	29 (737)		
Shipping Depth - in (mm)	32 3/4 (832)		
Shipping Height - in (mm)	80 (2032)		
Available Agency Approvals	Elec: ^c UL _{US} , Gas: ^c CSA _{US}		

* Information shown applies to highest end control available
 Note: Not all options are available for all models. Twelfth digit in model number indicates US or Canadian unit. C=Canada & T=US.
 Refer to the price list for the available models and options.
 Lower unit is ADA compliant

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management system of Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

©Copyright 2018 Alliance Laundry Systems LLC

AH18-0026

